

T1800 1000V Analogue

- Heavy duty carry case
- Analogue display
- Taut band movement
- Auto discharge
- Colour coded scale
- Live circuit indication
- AC Voltage measurement

NEW ROBUST DESIGN



Technical Specification

Test Voltages and measuring range	250V 0-100MΩ 500V 0-200MΩ 1000V 0-400MΩ
Short circuit terminal current	145mA DC Approx
Output Voltage on open circuit	Rated test voltage + 10%
Short Circuit Current (Max)	2mA DC
Continuity Range	0 - 50Ω
Open circuit terminal voltage	445mV DC Approx
Voltage Measurement	0 - 500 VAC
Accuracy	
Voltage	± 2% of scale length
Insulation	± 5% of Indicated value



Meter Supplied With Certificate of Conformance

Model Specification

Dimensions (mm)	170(L) x 165(W) x 92(H)
Power Source	8 x 1.5V AA Batteries
Weight	1000g

T1832 1000V Analogue

- Taut band movement
- Live circuit indication
- 200mA continuity short circuit current
- Auto discharge
- AC voltage measurement
- Rugged construction
- Nulling of test leads
- Continuity buzzer
- Mirror scale

NEW ROBUST DESIGN



Technical Specification

Test Voltages and measuring range	250V 0-100MΩ 500V 0-200MΩ 1000V 0-400MΩ
Short circuit terminal current	210mA DC Approx
Output Voltage on open circuit	Rated test voltage + 10%
Short Circuit Current (Max)	1.3mA
Continuity Range	3Ω - 500Ω
Open circuit terminal voltage	445mV DC Approx
Voltage Measurement	0 - 500 VAC
Accuracy	
Voltage	± 3% of scale length
Insulation	± 5% of Indicated value



Meter Supplied With Certificate of Conformance

Model Specification

Dimensions (mm)	170(L) x 165(W) x 92(H)
Power Source	8 x 1.5V AA Batteries
Weight	1030g

T1132 1000V Analogue

- Safety voltmeter protection
- Live circuit indication
- Auto discharge
- AC voltage measurement
- Zero adjustment knob

COMPACT DESIGN



Meter Supplied With Certificate of Conformance

Technical Specification

Insulation Test Voltage	250,500,1000V
Insulation Resistance	250V (100MΩ) 500V (200MΩ) 1000V (400MΩ)
AC Voltage	0 to 600V
Ohm meter	3 to 500Ω
Test Current	205mA

Model Specification

Dimensions (mm)	175(L) x 85(W) x 75(H)
Power Source	8 x 1.5V AA Batteries
Weight	655g

T1851 1000V Digital

- Continuity buzzer
- Live circuit warning
- 210mA continuity short circuit current
- AC voltage measurement
- Auto power off
- Large display
- Auto discharge
- Live circuit indication

NEW ROBUST DESIGN

3 1/2 Digits
2000 Counts



Meter Supplied With Certificate of Conformance

Technical Specification

Test Voltages and measuring range	250V 0-200MΩ 500V 0-200MΩ 1000V 0-2000MΩ
Short circuit terminal current	210mA DC Approx
Output Voltage on open circuit	Rated test voltage + 10%
Short Circuit Current (Max)	1mA
Continuity Range	0-2kΩ
Open circuit terminal voltage	4V DC Approx
Voltage Measurement	0 - 500 VAC
Accuracy	
Voltage	± 1.5 % + 3 Digit
Insulation	± 1.5 % + 5 Digit

Model Specification

Dimensions (mm)	170(L) x 165(W) x 92(H)
Power Source	8 x 1.5V AA Batteries
Weight	1040g