

T890 Safety 3 phase Detector (Non contact)

- Clamps over wire insulation without contact on conductor
- Auto off
- Non contact sensor clips
- Open phase and phase sequence
- Magnets on back of unit to mount on metal surfaces



CAT III
1000V
IEC61010-1

Meter
Supplied With
Certificate of
Conformance

Technical Specification

Operating Voltage	150 to 1000VAC
Operating Frequency	45 to 65Hz
Circuit Structure	Electronic
Operating Temp	-10°C to 50°C
Humidity	80%
Power Source	4 x 1.5 AA Batteries
Current consumption	15mA
Cable Length	Approx 800mm

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	118(L) x 69(W) x 38(H)
Weight	370g

T855 3 phase Rotation Indicator

- Fused test leads
- Rotating disc
- Colour coded Red/White/Blue
- Large alligator clips



Meter
Supplied With
Certificate of
Conformance

Technical Specification

Operating Voltage	90 - 600 VAC
Operating Frequency	50/60 Hz
Operating Temp & Humidity	-10°C to 40°C at 80% Max relative humidity
Cord	1.1m each of Red(R), white(S) & Blue(T)

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	106(L) x 75(W) x 40(H)
Weight	515g

T860 3 phase & Motor Rotation indicator

- Determine rotation of unconnected motors
- Heavy duty alligator clips
- Open phase identification



Meter
Supplied With
Certificate of
Conformance

Technical Specification

Operating Voltage	100 to 600VAC
Operating Frequency	45 to 75Hz
Circuit Structure	Electronic
Operating Temp	0°C to 50°C at 90° &
Humidity	Max relative Humidity
Power Consumption (Correct)	± 14mA for motor rotation field test ±7mA for Phase rotation field indication

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	153(L) x 72(W) x 35(H)
Weight	182g

T887 3 phase Rotation LCD Indicator

- Indicates phase rotation and phase presence
- Colour coded Red/White/Blue
- Large alligator clips



Meter
Supplied With
Certificate of
Conformance

Technical Specification

Operating Voltage	40 - 700 VAC
Operating Frequency	50/60 Hz
Operating Temp & Humidity	-1°C to 55°C Not in full sunlight
Cord	60cm each of Red(R), white(S) & Blue(T)

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	150(L) x 72(W) x 34(H)
Weight	159g