

Digital Clamp Meters

T98 1000A AC

- Jaw size 42mm
- Backlight
- Continuity
- Data hold



Technical Specification

AC Current	20,200,1000A
DC Voltage	1000V
AC Voltage	750V
Resistance	200,2000Ω
Temperature	-40°C to 750°C
Accuracy	
AC Current	±2.0% + 5 Digit
DC Voltage	±1.0% + 2 Digit
AC Voltage	±1.0% + 5 Digit
Resistance	±1.0% + 3 Digit
Temperature	±1.0% + 5 Digit

Model Specification

Accessories	Carry Pouch, Temp Probe
Dimensions (mm)	250(L) x 99(W) x 43(H)
Power Source	9V Battery
Weight	460g

**3 ⁻¹/₂ Digits
1999 Counts**

**T260D 1000A AC
Combination Clamp**

- Jaw size 60mm
- Diode
- Continuity buzzer



Technical Specification

AC Current	20,200,1000A
AC Voltage	200,750V
DC Voltage	200m,20,200,1000V
Resistance	200,2K,20K,200K,2MΩ
Accuracy	
DC Voltage	±0.5% + 1 Digit
AC Voltage	±1.2% + 10 Digit
AC Current	±2% + 5 Digit
Resistance	±1.0% + 2 Digit

Model Specification

Dimensions (mm)	230(L) x 70(W) x 37(H)
Power Source	9V Battery
Weight	310g

**3 ⁻¹/₂ Digits
1999 Counts**

**TBM116 1000A AC
Auto Check**

- Jaw size 45mm
- Diode
- Continuity
- Relative zero
- Data hold



**3 ⁻³/₄ Digits
4000 Counts**



Meter
Supplied With
Certificate of
Conformance

Technical Specification

AC Current	400,1000A
DC Voltage	400m,4,40,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,40MΩ
Accuracy	
DC Voltage	2% + 4 Digit
AC Voltage	3% + 5 Digit
AC Current	1.5% + 5 Digit
Resistance	1.2% + 4 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	220g

**TBM118 2000A AC
Auto Check**

- Jaw size 45mm
- Emf detection
- Diode
- Continuity
- Relative zero
- Data hold



**3 ⁻⁵/₆ Digits
6000 Counts**



Meter
Supplied With
Certificate of
Conformance

Technical Specification

AC Current	400,2000A
DC Voltage	6,60,600V
AC Voltage	6,60,600V
Resistance	6K,60K,600K,6MΩ
Frequency	10 to 50KHz
Capacitance	100n,1000n,10μ,100μ,2000μF
Accuracy	
DC Voltage	2% + 5 Digit
AC Voltage	1.5% + 5 Digit
AC Current	1.5% + 5 Digit
Resistance	1.2% + 4 Digit
Frequency	0.5% + 4 Digit
Capacitance	3.5% + 5 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	220g

**TBM135 1000A
AC Data Logger**

- Jaw Size 45mm
- Backlight
- 5400 Point Logging
- Record Function
- Continuity



**3 ⁻⁵/₆ Digits
6000 Counts**



Meter
Supplied With
Certificate of
Conformance

Technical Specification

AC Current	40,400,1000A
DC/AC Voltage	600V
Resistance	999,9Ω
Frequency	5 to 500Hz
Temperature	-50 to 300°C
Thd%-r	0.0%-99.9%
Accuracy	
DC Voltage	0.5% + 5 Digit
AC Voltage	1.5% + 5 Digit
AC Current	2.0% + 5 Digit
Resistance	1.0% + 6 Digit
Frequency	0.5% + 4 Digit
Temperature	2% + 3°C
Thd%-r	Fundamental 1% + 6 Digit 2-3 Harmonics 5% + 6 Digit 4-51 St Harmonics 2%

Model Specification

Optional Accessories	RS232 Cable & Software (TBR13X) See PG 9 for Adaptor
Accessories	Carry Pouch, Type-K Thermocouple
Dimensions (mm)	224(L) x 78(W) x 40(H)
Power Source	2x1.5V AAA Batteries
Weight	224g

T77N AC Earth Leakage

- Jaw Size 40mm
- High accuracy with no interference
- Data hold • Auto power off
- Low pass filter with high stability
- Autorange • Bargraph
- Auto back light sensor
- Frequency compare function



Technical Specification

AC Current	0.01mA,6mA,60A,100A
Accuracy	
AC Current	6mA ±1.0% rdg + 8 Digit 60A ±1.0% rdg + 8 Digit 100A ±2.0% rdg + 10 Digit

Model Specification

Dimensions (mm)	200(L) x 70(W) x 40(H)
Power Source	2 x 1.5V AAA Batteries
Weight	265g

**4 Digits
6000 Counts**