

T223 100A AC/DC Automotive

- Jaw size 12.5mm
- Concurrent Reading
- Resistance
- Continuity



Technical Specification	
AC/DC Current	1mA,10mA,10A,100A
AC/DC Voltage	0,1V, 600V
Resistance	1, 10kΩ
Accuracy	
AC/DC Current	± 2 % + 10 Digit
AC/DC Voltage	± 1,5 % + 5 Digit
Resistance	± 1 % + 3 Digit
Protection	
AC/DC Voltage	660Vrms
AC/DC Current	150A Rms

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	202(L) x 70(W) x 34(H)
Power Source	2 x 1.5V AA Batteries
Weight	180g

T809 200A AC/DC

- Jaw size 19mm
- Pocket size
- Auto power off
- Low battery indication
- Data hold



Technical Specification	
AC Current	40A,200A
DC Current	40A,200A
Accuracy	
AC Current	40A 0,01A ± 3% + 5 Digit 200A 0,1A ± 3% + 5 Digit
DC Current	40A 0,01A ± 2,5% + 8 Digit 200A 0,1A ± 2,5% + 8 Digit
Frequency	50Hz - 60Hz

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	150(L) x 50(W) x 25(H)
Power Source	2 x 1,5V Battery LR44 (T515BATT)
Weight	95g

3 ^{-3/4}/₄ Digits
4000 Counts

Meter
Supplied With
Certificate of
Conformance

TBM061 400A AC/DC

- Jaw size 30mm
- Diode
- Continuity
- Relative zero
- Auto power off



3 ^{-3/4}/₄ Digits
4000 Counts

CAT III
600V
IEC61010-1

LISTED



Meter
Supplied With
Certificate of
Conformance

Technical Specification	
AC/DC Current	0,01,400A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	1KHz to 100KHz
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC/DC Current	±2,5% + 5 Digit
DC Voltage	±1,0% + 4 Digit
AC Voltage	4,40,400V ±1,0% + 4 Digit 600V ±2,0% + 4 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4MΩ ± 1,0% + 4 Digit 40MΩ ± 2,0% + 4 Digit
Frequency	± 2,0% + 4 Digit
Capacitance	± 3,5% + 6 Digit

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	188(L) x 63(W) x 40(H)
Power Source	2 x AAA Batteries
Weight	218g

TBM062 400A AC/DC

- Jaw size 30mm
- Diode
- Continuity
- Relative zero
- Auto power off
- Back light



True
RMS

3 ^{-3/4}/₄ Digits
4000 Counts

CAT III
600V
IEC61010-1

LISTED



Meter
Supplied With
Certificate of
Conformance

Technical Specification	
AC/DC Current	0,01,400A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	1KHz to 100KHz
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC/DC Current	±2,5% + 5 Digit
DC Voltage	±1,0% + 4 Digit
AC Voltage	4,40,400V ±1,0% + 4 Digit 600V ±2,0% + 4 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4MΩ ± 1,0% + 4 Digit 40MΩ ± 2,0% + 4 Digit
Frequency	± 2,0% + 4 Digit
Capacitance	± 3,5% + 6 Digit

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	188(L) x 63(W) x 40(H)
Power Source	2 x AAA Batteries
Weight	218g

TBM189 600A AC/DC

- Jaw size 30mm
- Variable frequency drives
- Ghost voltage detection
- Dual display
- In-Rush crest
- EF Detection



Includes
Temp
Probe

True
RMS

3 ^{-1/2}/₂ Digits
1900 Counts

CAT III
600V
IEC61010-1

Meter
Supplied With
Certificate of
Conformance

Technical Specification	
AC/DC Current	60, 600A
AC Voltage	600V
DC Voltage	600V
Resistance	600,6K,600K,6M,40MΩ
Frequency	10Hz to 400Hz
Temperature	-50°C to 1000°C
Capacitance	60n,600n,60μ,2000μF
Accuracy	
AC/DC Current	± 1.5 % + 6 Digit
AC Voltage	± 1.2 % + 5 Digit
DC Voltage	± 0.5 % + 5 Digit
Resistance	± 0.5 % + 5 Digit
Low Pass Filter	± 3.5 % + 80 Digit
Temperature	± 0.3 % + 4 Digit
Capacitance	± 2 % + 5 Digit

Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	2 x 1.5V AAA Batteries
Weight	227g

TBM079 600A AC/DC AmpTip™ Jaws

- Jaw size 35mm
- AmpTip™ low current range
- Large LCD display
- Back light
- 3 Phase rotation for mains
- 3 Phase rotation for motors
- Temperature
- EF Detection
- Rotary selector switch
- Continuity
- Data hold



True
RMS

NEW

3 ^{-3/6}/₆ Digits
6000 Counts

Includes
Temp
Probe

CAT III
600V
IEC61010-1

LISTED



Meter
Supplied With
Certificate of
Conformance

Technical Specification	
AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	600,6K,600KΩ
Frequency	50Hz to 400Hz
Temperature	-40°C to 400°C
Capacitance	200μ,2500μF
Accuracy	
AC Current	±1,8% + 5 Digit
DC Voltage	±1,0% + 5 Digit
AC Voltage	4,40,400V ± 1,5% + 5 Digit 600V ± 1,2% + 7 Digit
Resistance	4K,40K,400KΩ ± 0,6% + 4 Digit 4mΩ ± 1,0% + 4 Digit 40mΩ ± 2,0% + 4 Digit
Frequency	±0,5% + 4 Digit

Model Specification	
Accessories	Carry Pouch, Temp probe
Dimensions (mm)	223(L) x 76(W) x 37(H)
Power Source	2 x 1.5V AAA
Weight	234g