

**TBM195 2000A AC/DC
(CAT IV)**

- Jaw Size 55mm
- Large display
- Dual display
- Non contact EF detection
- VFD (Variable frequency drives)
- Relative zero
- Autocheck
- Diode



Technical Specification

AC/DC Current	100, 200, 500, 1000, 2000A
AC Voltage	6, 60, 600, 1000V
DC Voltage	6, 60, 600, 1000V
Resistance	600, 6K, 60K, 6M, 40MΩ
Capacitance	60n, 6μ, 60μ, 600μ, 2000μF
Accuracy	
AC/DC Current	± 2 % + 5 Digit
AC Voltage	± 1.2 % + 5 Digit
DC Voltage	± 0.5 % + 5 Digit
Resistance	± 0.5 % + 5 Digit
Capacitance	± 2.0 % + 5 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	264(L) x 97(W) x 43(H)
Power Source	2 x 1.5V AAA Batteries
Weight	608g

Meter
Supplied With
Certificate of
Conformance

CAT IV
1000V
IEC61010-1

3 ³/₆ Digits
6000 Counts

**TBM197 2000A AC/DC
(CAT IV)**

- Jaw Size 55mm
- Large display
- Back light
- Dual display
- Non contact EF detection
- VFD (Variable frequency drives)
- Relative zero
- Autocheck
- Diode



AC/DC Current	100, 200, 500, 1000, 2000A
AC Voltage	6, 60, 600, 1000V
DC Voltage	6, 60, 600, 1000V
Resistance	600, 6K, 60K, 6M, 40MΩ
Capacitance	60n, 6μ, 60μ, 600μ, 2000μF
Temperature	-50°C to 1000°C
Accuracy	
AC/DC Current	± 2 % + 5 Digit
AC Voltage	± 1.4 % + 7 Digit
DC Voltage	± 1.4 % + 7 Digit
Resistance	± 0.5 % + 5 Digit
Capacitance	± 2.0 % + 5 Digit
Temperature	± 0.3 % + 4 Digit

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	264(L) x 97(W) x 43(H)
Power Source	2 x 1.5V AAA Batteries
Weight	608g

Meter
Supplied With
Certificate of
Conformance

CAT IV
1000V
IEC61010-1

3 ³/₆ Digits
6000 Counts

True RMS

Includes
Temp
Probe

T2608 2000A AC/DC

- Jaw Size 57mm
- Min/Max
- Data hold / Peak hold
- Bargraph
- Auto Power OFF
- Diode
- Continuity



Technical Specification

DC Current	400, 2000A
AC Current	400, 1500A
AC Voltage	400m, 4, 40, 400, 750V
DC Voltage	400m, 4, 40, 400, 1000V
Resistance	400, 4k, 40k, 400k, 4m, 40MΩ
Capacitance	4n, 40n, 400n, 4μ, 40μF
Frequency	10, 1K, 10K, 100K, 400KHz
Accuracy	
AC/DC Current	±1.5% rdg + 5 Digit
AC Voltage	±1.5% rdg + 4 Digit
DC Voltage	±0.5% rdg + 1 Digit
Resistance	±1.0% rdg + 4 Digit
Frequency	±0.1% rdg + 4 Digit
Capacitance	±1.0% rdg + 4 Digit

Model Specification

Dimensions (mm)	277(L) x 102(W) x 49(H)
Power Source	9V Battery
Weight	540g

Meter
Supplied With
Certificate of
Conformance

CAT III
1000V
IEC61010-1

3 ³/₆ Digits
4000 Counts

T2000 Earth Resistance Clamp



- Jaw Size 32mm • 99 Memory locations
- Resistance measurement on earth probes by means of ground loop method
- Direct measurement on earth probes without any cable breaking
- Measurement of leakage current on earth installations
- Setting of alarm thresholds on measurements
- Storage of measurement results
- Detection of current noise on measurements
- Data HOLD function • Backlight • Auto Power OFF



Technical Specification

Resistance	0.01Ω-0.999Ω	±(1.0%+0.01Ω)	0.001Ω
	0.10Ω-0.99Ω	±(1.0%+0.01)	0.01Ω
	1Ω-49.9Ω	±(1.5%+0.1Ω)	0.1Ω
	50.0Ω-99.9Ω	±(2.0%+0.3Ω)	0.5Ω
	100Ω-199.9Ω	±(3.0%+1Ω)	1Ω
	200Ω-395Ω	±(6.0%+5Ω)	5Ω
	400Ω-590Ω	±(10%+10Ω)	10Ω
Current	600Ω-1000Ω	±(20%+20Ω)	20Ω
	0.00A-80mA	±(2.5%+1mA)	0.05mA
	80-650mA	±(2.5%+2mA)	0.5mA
	650-999.5mA	±(2.5%+0.003A)	1.5A
	1.000-3.995mA	±(2.5%+0.01A)	0.005A
4.00-20.00mA	±(2.5%+0.05A)	0.01A	

Model Specification

Dimensions (mm)	293(L) x 90(W) x 66(H)
Accessories	Resistive test loop, carry case
Weight	1320g

Meter
Supplied With
Calibration
Certificate

CAT III
150V
IEC61010-1

